



Total Access 1500

Narrowband Multiservice Access Platform

Product Features

- POTS, specials, and data supported
- Up to 96 two-wire interfaces
- Compact (2U) mounting for crowded COs or RTs
- Fully redundant commons
- TR-08 signaling fully compatible with SLC®-96
- Up to five times as dense as a D4 channel bank when used for specials
- TL1 interface to NMA™ over X.25
- SNMP management
- Integrated digital and metallic test access
- Mechanized Loop Testing (MLT)
- Redundant power feeds
- NEBS Level 3 and UL 1950 compliant
- Industry-leading 10-year warranty

The ADTRAN™ Total Access® 1500 is a **Carrier-Class, multiservice access platform for deploying narrowband services from TDM network access.** A compact, versatile platform, Total Access 1500 integrates the functionality of many Carrier products into a single high-density chassis. Total Access 1500's small footprint (2U-high mounting) makes it the perfect choice for integrated communications providers such as ILECs, CLECs, and ISPs who need to deploy services from crowded Remote Terminals (RTs), Central Offices (COs), or Co-Location (COLO) facilities.

Total Access 1500 provides a variety of services including POTS, special services (ISDN, DDS, FXO, FXS, E&M, DPO, DPT, and PLAR), and data services. Total Access 1500 complements ADTRAN's Total Access 3000 broadband multiservice access platform, which can terminate and distribute higher bandwidth services such as SONET, DS3, HDSL, HDSL2, T1, and optical DS2. Total Access 1500 can be deployed as a:

- Small Digital Loop Carrier (DLC), for a simple and effective means of deploying POTS (up to 96 lines in a 2U mounting)
- Special services delivery platform, with up to five times the density of any competing platform (D4)
- IAD, serving up to 96 customers with voice and data services

Total Access 1500 is a modular device with five common slots and 24 access slots. Common units required for operation are a Power Supply Unit (PSU), a Line Interface Unit (LIU), and a System Controller Unit (SCU). A second, redundant PSU and LIU may be deployed for added reliability. The PSU is available with an integrated ring generator providing up to 40 REN ringing capacity. The LIU can support up to four T1 interfaces and has full Time Slot Assignment (TSA) capability. This feature allows users to "steer" varied amounts of bandwidth from the network to any of the access slots, ensuring that no bandwidth is stranded. The 24 access slots accept a variety of voice and data access modules, allowing users to optimize their service for each application.

Using local or remote inband management, service providers can provision and monitor the bank's network interface and access modules. Transaction Language 1 (TL1) protocol is used to communicate with Telcordia's NMA Operations Support System (OSS) using an internal X.25 PAD. An Ethernet 10BaseT connector is used for connection to SNMP networks and Telnet. ADTRAN's ADVISION™ software, run on a Hewlett-Packard Openview workstation, provides a graphical user interface (GUI).

Total Access 1500 is designed for 23-inch relay racks. Full compliance with NEBS Level 3 and UL 1950 ensures maximum reliability and safety.



Total Access 1500



Narrowband Multiservice Access Platform

Product Specifications

Mechanical

- **Dimensions:** 3.5 in. H X 23 in. W X 11 in. D
- **Weight:** 12 lbs. (chassis only)

Network Interfaces

- **Transport:** DS1
- **Capacity:** 1 to 4 T1 plus 1 protect T1
- **Line Rate:** 1.544 Mbps +/- 75 bps
- **Physical interface:** Wire wrap
- **Framing:** D4 (SF)/ESF, TR-08
- **Line code:** AMI/B8ZS
- **Input signal:** 0 to -36 dB
- **DSO assignment:** User-selectable
- **T1 transmit timing:** Loop, local, external
- **TR-08 Support:** Single Party Ringing (SPR) and Universal Voice Grade (UVG) analog ports supported with FXS modules. CLASS® services.

Testing and Troubleshooting

- **Local:** Payload and line loopback
- **Remote:** Payload and line loopback

Network Interface Test Jacks

- **Bantam jacks:** RXMON, TXMON

Performance Monitoring

- **Error counts:** ES, SES, UAS, %, AS, %, EFSEC, alarms, and error rates
- **Reports:** NI information stored for last 24 hours (in 15-minute increments)

Electrical

- **DC Power:** -40 to +56 VDC
- **Connection:** Screw terminals (A and B feed)

Regulatory Standards

- NEBS Level 3
- UL 1950
- FCC Part 15 (Class A) and Part 68

Management

Craft Interface

- Accessible from front of SCU
- **Electrical interface:** EIA-232, PC serial port, or modem
- **Physical connector:** DB-9 front

10BaseT Port

- SNMP/TELNET

X.25

- TL1

Environmental

- **Operating temperature:** -40°C to +65°C
- **Storage temperature:** -20° to +70° C
- **Relative humidity:** Up to 95 percent, noncondensing

Ordering Information

Equipment	Part #
Chassis and Commons	
Total Access 1500 Chassis	1180001L1
PSU	1180007L2
PSU/RG	1180007L1
LIU 4T1+Protect	1180109L1
LIU 2T1	1180009L1
Universal SCU	1180008L1
SCU COT with MLT	1180008L2
SCU RT with MLT	1180008L3
Single Access Modules	
Single E&M/T0	1180402L1
Single FXS/DPO/PLAR	1180403L1
Single FXO/DPT	1180404L1
Single OCU DP	1180005L1
Single DSO DP	1180003L1
Single U-BR1TE	1180020L1
Single Total Reach DDS DP	1180105L1
Single FT1 DP	1180405L1
Dual Access Modules	
Dual DSO DP	1180203L2
Dual OCU DP	1180205L2
Dual FXS/DPO/PLAR	1180208L2
Dual FXO/DPT	1180207L2
Dual V.35	1180025L1
Quad Access Modules	
Quad FXO/C-POTS	1175407L2
Quad FXS/R-POTS with MLT	1180408L1
Accessories	
AC Power Converter/Battery Charger	1180043L1
Battery Backup System	1175044L1
Wall Mount Brackets	1180046L1



ADTRAN, Inc.
901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963 8000 voice
256 963 8030 fax
877 457 5007 fax back

General Information
800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales

Technical Support

888 5ADTRAN
support@adtran.com
www.adtran.com/support

Where to Buy

800 827 0807
www.adtran.com/where2buy

Post-Sales

Technical Support

800 726 8663
support@adtran.com
www.adtran.com/support

Regional Offices

Dallas, TX
972 830 9070
Denver, CO
303 471 9150
Irvine, CA
949 260 3500
Kansas City, KS
800 471 8649
Newark, NJ
800 471 8656
Ontario, Canada
416 290 0585
Quebec, Canada
877 923 8726
San Antonio, TX
888 223 7671

International Inquiries

256 963 8000 voice
256 963 6300 fax
international@adtran.com
www.adtran.com/international



I.S. EN ISO 9001
ADTRAN is an
ISO 9001:2000 registered company.



TL 9000
ADTRAN is a
TL 9000 registered company.

61180001L1-8D April 2003

Copyright © 2003 ADTRAN, Inc.
All rights reserved.

Specifications are subject to change without notice. ADTRAN and ADVISION are trademarks of ADTRAN, Inc. Total Access is a registered trademark of ADTRAN, Inc. All other registered trademarks and trademarks mentioned in this publication are the property of their respective owners.