

NT1 ACE³

Triple NT1

Product Features

- Three NT1s in a single enclosure
- Optimized for 384 Kbps videoconferencing applications
- Supports multiple switch vendors; LUCENT 5ESS™, NT1 DMS-100™, Siemens EWSD, NEC, and National ISDN-1
- LED display to indicate power and network status
- Provides U-interface lightning protection
- Standard five-year warranty

The NT1 ACE³™ combines the functionality of the **three NT1s in a single device**. Connection to the ISDN network is accomplished via three U-interfaces, and connection to the subscribers' terminal equipment utilizing three S/T-interfaces. The U- and S/T-interfaces on the NT1 ACE³ conform to ANSI and CCITT standards and perform all Layer 1 functions.

The NT1 ACE³ is designed with aesthetics as well as functionality in mind. The unit is enclosed in an attractive, durable plastic housing appropriate for desktop or wall-mount use. The NT1 ACE³ is powered by the external power supply provided with the unit.

The NT1 ACE³ provides 100 ohm bus termination and is protected from lightning and harmful line transients on the network interfaces.

Six LED status indicators on the NT1 ACE³ aid in fault isolation. Indicators display the status for Power, Network Ready, Network and Customer Errors, and Network Test.



ADTRAN, Inc.

Attn: Enterprise Networks
901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963-8000 voice
256 963-8699 fax
256 963-8200 fax back

General Information
800 9ADTRAN
info@adtran.com
www.adtran.com

**Pre-Sales
Technical Support**
800 615-1176 toll-free
application.engineer@adtran.com
www.adtran.com/support

Where to Buy
877 280-8416 toll-free
channel.sales@adtran.com
www.adtran.com/where2buy

**Post-Sales
Technical Support**
888 423-8726
support@adtran.com
www.adtran.com/support

**ACES Installation &
Maintenance Service**
888 874-ACES
aces@adtran.com
www.adtran.com/support

International Inquiries
256 963 8000 voice
256 963-6300 fax
international@adtran.com
www.adtran.com/international

**For the regional office
nearest you, visit:**
www.adtran.com/where2buy

NT1 ACE³

Triple NT1

Product Specifications

NT1 ACE³ Interface

Network

- **Line:** 2-wire (TIP and Ring)
- **Operating Mode:** full-duplex
- **Data Rate:** 160 Kbps total; 144 Kbps available to customer
- **Signal Format:** 2B1Q
- **Output Amplitude:** 2.5 V, zero-to-peak
- **Tx Source Impedance:** as per ANSI T1.601-1992
- **Rx Source Impedance:** as per ANSI T1.601-1992
- **Receiver Sensitivity:** as per ANSI T1.601-1992

Customer

- **Line:** 4-wire (Tx and Rx pair)
- **Operating Mode:** full-duplex
- **Data Rate:** 192 Kbps total; 144 Kbps available to customer
- **Signal Format:** Alternate mark inversion, 100% duty cycle
- **Output Amplitude:** 0.75 V, zero-to-peak
- **Tx Source Impedance:** as per ANSI T1.605-1991
- **Rx Source Impedance:** as per ANSI T1.605-1991
- **Receiver Sensitivity:** as per ANSI T1.605-1991

Switch Compatibility

- Lucent 5ESS™
- Nortel DMS-100™
- Siemens EWSD
- NEC
- National ISDN-1

Agency Approvals

- FCC Part 15, Class B
- FCC Part 68
- UL
- CUL
- CSA
- CS03

Environment

Operating Temperature

- 0° to 50°C (32° to 122°F)

Storage Temperature

- -20° to 70°C (-4° to 158°F)

Relative Humidity

- Up to 95%, non-condensing

Physical

Size

- 1.625" H, 6.375" D, 9.0" W

Weight

- 9.5 oz

Power


- +12 vDC, 3.3 W dissipation

Product Includes

- Two 6 ft TRI telephone cables (RJ45 to RJ11)
- 110 V wallmount power supply
- User Manual

Ordering Information

Equipment	Part #
NT1 ACE ³	1200236L1



I.S. EN ISO 9001
ADTRAN is a
ISO 9001 registered company.



TL 9000
ADTRAN is a
TL 9000 registered company.

Printed in the U.S.A.
61200236L1-8C July 2002
©2002 ADTRAN, Inc. All rights reserved.

Specifications subject to change without notice. ADTRAN is a trademark of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.