



OC-3 Multiplexer

Total Access OPTI-3 Single OC-3 to Three DS3

Product Features

- One GR-253 compliant OC-3 port, three DS3 ports
- 1+1 optical and 1:1 electrical protection, 1+1 SONET Automatic Protection Switch (APS)
- Interoperable with industry-standard SONET multiplexers
- Two or, with redundancy, four SM fibers at 1310 nm over a 40 km range or 1550 nm over an 80 km range
- DS3 signals, channelized/unchannelized
- Space-saving wallmount chassis (WMC) or a one rack unit high 19-in. or 23-in. rack-mounted chassis (RMC)
- Single card, hot swappable solution increases reliability and reduces cost
- Management functions over the DCC, TL-1 (including GNE), and SNMP
- Local craft port interface for local management and Telnet for remote menu operation
- Telcordia OSMINE compliant and NMA (via DCC) supported
- Alarm history
- Management of subtended units via IP/DCC
- NEBS Level 3 compliant
- Industry-leading 10-year warranty

The ADTRAN™ Total Access® OPTI-3™ sets a new mark for OC-3 multiplexers, delivering three DS3 circuits from a single OC-3 feed.

Designed to meet the growing demand for DS3 deployment in today's economy, the Total Access OPTI-3 eliminates the need for expensive SONET multiplexer equipment in terminal mode applications and provides the fullest use of OC-3 capacity.

The Total Access OPTI-3 is interoperable with other SONET devices complying with GR-253 for easy deployment in new and existing SONET networks. A carrier-class device, the Total Access OPTI-3 meets the needs of applications that require extended temperature range operation such as remote terminals. The fully integrated design supports optional redundancy and is easily managed with support for TL1 commands over the Data Communications Channel (DCC). Additional management features include a local craft interface, remote alarm transport via DCC, and alarm reporting to legacy alarm systems. Front panel LEDs conveniently display status information.

The unit requires only a fraction of the footprint normally needed for optical deployments. The Total Access OPTI-3 occupies standard slots in either a small two rack unit high wallmount chassis (WMC) or a space-saving one rack unit high rackmount chassis (RMC). The Total Access OPTI-3 can also be configured to operate redundantly with optional protection. It can upgrade online from unprotected to protected status.

The DS3 BNC coax connectors are located on the rear of the Total Access OPTI-3 chassis. This permits easy access to the customer side of the network for a convenient demarcation point, or to extend services to DS3 multiplexer applications. The fiber optics enter the chassis from the front of the unit and terminate on the card with a dual SC connector for simple installation. The unit provides for external auxiliary alarm inputs, and the RMC chassis provides additional alarm outputs for CO alarms.



ADTRAN, Inc.
901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 14000
Huntsville, AL 35814-4000

256 963 8000 voice
256 963 8030 fax
877 457 5007 fax back

General Information
800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales Technical Support
888 5ADTRAN
support@adtran.com
www.adtran.com/support

Where to Buy
800 827 0807
www.adtran.com/where2buy

Post-Sales Technical Support
800 726 8663
support@adtran.com
www.adtran.com/support

Regional Offices
Dallas, TX
972 830 9070
Denver, CO
303 471 9150
Irvine, CA
949 260 3500
Kansas City, KS
800 471 8649
Newark, NJ
800 471 8656
Ontario, Canada
416 290 0585
Quebec, Canada
877 923 8726
San Antonio, TX
888 223 7671


International Inquiries
256 963 8000 voice
256 963 6300 fax
international@adtran.com
www.adtran.com/international

I.S. EN ISO 9001
ADTRAN is an
ISO 9001:2000 registered company.

TL 9000
ADTRAN is a
TL 9000 registered company.

Printed in the USA
6118400XL1-8C May 2003
©2003 ADTRAN, Inc. All rights reserved.

Total Access OPTI-3 Single OC-3 to Three DS3



Product Specifications

Front Panel Features

LEDs

- Board status
- Optics status
- DS3-1
- DS3-2
- DS3-3
- ACO

Switches

- ACO
- Test/APS enable
- APS
- Craft interface connector

Mechanical

- Dimensions of Wallmount Chassis: 3.5 in. H x 6 in. W x 12 in. D
- Mountings: Wall, shelf, or cabinet mountable
- Dimensions of 19 in. and 23 in. Chassis: 1.75 in. H x 13.5 in. W x 12 in. D

Interfaces

- Single OC-3 Standard optical interface to network with dual SC connector
- GR-253 compliant, 1310 nm or 1550 nm
- 3 DS3 level signals with standard 75 ohm BNC connectors, DS3 or DS3 UNI
- 2 BITS clock inputs, wire wrap

Electrical

Power Requirements

- -48 VDC nominal (-42 to -56 VCC) or +24 VDC nominal (+22 to +26 VDC) or -24 VDC nominal (-22 to -26 VDC)
- 8.5 watts nominal @ -48 VDC

Regulatory Standards

- NEBS Level 3
- UL 1950
- GR-1089-CORE
- FCC Part 15

Environmental

Operating Temperature

- -40°C to +65°C for 19-in. and 23-in. rackmount chassis
- -40°C to +50°C for wallmount chassis

Storage

- -40°C to +85°C for 19-in. and 23-in. rackmount chassis
- -40°C to +70°C for wallmount chassis
- Relative Humidity: 5 to 95 percent, noncondensing

Ordering Information

Equipment	Part #
OPTI-3 wallmount chassis	1184001L1
OPTI-3 card (1310 nm)	1184002L3
OPTI-3 card (1550 nm)	1184002L4
OPTI-3 19 in. or 23 in. rackmount chassis	1184003L1
Bundles	
WMC OPTI-3 with redundancy	4184001L1
RMC OPTI-3 with redundancy	4181003L1
WMC OPTI-3 no redundancy	4184001L2
RMC OPTI-3 no redundancy	4184003L2
WMC OPTI-3 with redundancy and battery backup	4184001L3
RMC OPTI-3 with redundancy and battery backup	4184003L3

Specifications are subject to change without notice. ADTRAN is a trademark and Total Access is a registered trademark of ADTRAN, Inc. All other registered trademarks and trademarks mentioned in this publication are the property of their respective owners.